



ITC

Make Life Easier

Shenzhen ITC Technology Co.,Ltd

Email:info@itc-a.com

Call:86-755-2335-4846

Web:www.itc-a.com

Add:1-3F, No. 52, Ditang Road, Sha San Community, Shajing Street, Bao'an District, Shenzhen, China 518104



Shenzhen ITC Technology Co.,Ltd



ABOUT COMPANY

Shenzhen ITC Technology Co., Ltd. was founded in 2007 and is situated in Shenzhen, China. It is a high-tech enterprise that combines research and development, production, and sales. The company's main products cover a wide range, including power banks, wireless chargers, Bluetooth speakers, and other peripheral accessories for computers and mobile phones.

In recent years, in order to enhance the safety and stability of power banks, we have stepped up the development and application of new-generation battery technologies, namely lithium iron phosphate batteries, as well as solid and semi-solid batteries, in the power bank industry. In the future, the company plans to further expand its product portfolio to incorporate fast charging solutions, outdoor energy storage products, and new energy products. Our development objective is to become a leading expert in the field of next-generation mobile power banks.

With 18 years of rich experience in research and development, production, and export, we have grown into one of the most professional and competitive manufacturers in the industry. Our customers are spread across the globe, including those from the United States, Europe, the Middle East, Southeast Asia, and other regions. They consist of promotional companies, agents, brand owners, supermarkets, and chain stores. Notable clients include Walmart, Timberland, Nautica, Kooba, Steve Madden, Mont Blanc, JMC, Costco, and GreenHouse, among others.

ITC boasts a 2,000m² SMT workshop equipped with two state-of-the-art Japanese SMT machines. Additionally, it has an 8,000m² injection and assembly workshop with a workforce of over 300 employees. The company is also equipped with 12 sets of mold machines, 11 sets of injection molding machines, and 16 assembly production lines, enabling a daily production capacity of approx 60,000 units. Moreover, 20 sets of fully automatic aging equipment are available, which can conduct aging tests on 10,000 finished products simultaneously.

Our strong R&D team, consisting of around 15 employees, includes senior design engineers, senior hardware and software engineers, testing engineers, and other technical members, which significantly enhances our technological strength. Our R&D team is always committed to innovation and creation. We develop over 200 product models and 5 to 6 new exclusive molds every month.

ITC has successfully passed the audits of ISO9001, ISO14001, BSCI, and AF. All products manufactured by ITC comply with international certifications such as CE, FCC, RoHS, PSE, UL, CNS, KC, CB, and Qi. Every incoming material undergoes strict inspection before production and assembly, and the finished products are subjected to professional aging tests. With extensive experience in this industry, we are devoted to offering high-quality products and excellent design solutions to all our customers.

"Growing together with our customers" is our business philosophy. We always give top priority to our customers' interests and strive to achieve development and profitability by optimizing product quality. We firmly believe that the quality we provide today serves as the cornerstone for tomorrow's market success.

CONTENTS

POWER BANK WITH TWS 01

MAGNETIC WIRELESS POWER BANK 02&07-10

POWER BANK WITH BUILT-IN CABLE 03-05&11-13

SOLAR POWER BANK 06

14 POWER BANK WITH LiFePO₄ BATTERIES

15-20 POWER BANK

21-22 MINI POWER BANK DOCKING STATION

23-29 35W-140W ULTR-FAST CHARGING POWER BANK



ENJOY AND POWER
ON-THE-GO

POWER BANK
WITH TWS



ITC-PBW01

10000mAh(105555*2)

Specs: 22.5W
Size: 101.1*62.4*24mm

ITC-PBW02

10000mAh(105555*2)

Specs: 22.5W+15W
Size: 101.1*62.4*24mm

Specifications

22.5W

Material: ABS
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A(22.5W Max.)
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)

Specifications

22.5W+15W

Material: ABS
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A(22.5W Max.)
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)
Wireless Output 5W/7.5W/10W/15W(Max)

VM01-10000mAh

3-in-1 Magnetic Wireless Charger
For iPhone / Apple Watch / AirPods
Built-in Flat Braided Cable
Mobile Phone Holder
QSSB Batteries Optional



VM02-10000mAh



Input: Type-C 5V/2.6A 9V/2A 12V/1.5A(18W Max.)
Input: Built-in Type-C 5V/2.6A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (22.5W Max.)
Output: USB 5V/3A 9V/2A 12V/1.67A, 10V/2.25A, 12V/1.5A (22.5W Max.)
Wireless Output 2.5W/5W/7.5W/10W/15W
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A, 10V/2.25A(22.5W Max.)
Output: Built-in Lightning 5V/2.4A(12W Max.)

V04-20000mAh

22.5W / PD 20W
LCD Digital Display
Built-in Cable
10000mAh / 20000mAh
QSSB Batteries Optional



V01-10000mAh



POWER BANK WITH BUILT-IN CABLE



ITC-V05
10000mAh(145675*1)

Specs: 22.5W
Size: 99*62*16.7mm



ITC-V06
20000mAh(145675*2)

Specs: 22.5W
Size: 99*61.6*30.5mm



ITC-V01
10000mAh(126280*1)

Specs: 22.5W
Size: 107.9*68.9*15.3mm



ITC-V02
20000mAh(126280*2)

Specs: 22.5W
Size: 109*69.2*28.1mm



ITC-V03
10000mAh(126280*1)

Specs: 22.5W
Size: 107.9*68.9*15.3mm



ITC-V04
20000mAh(126280*2)

Specs: 22.5W
Size: 109*69.2*28.1mm

Specifications

22.5W

Material: Aluminum alloy
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A(22.5W Max.)
Output: USB 5V/3A 9V/2A 12V/1.67A 10V/2.25A 12V/1.5A(22.5W Max.)
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)
Output: Built-in-Lightning 5V,2A(10W)

Specifications

22.5W

Material: ABS
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A(22.5W Max.)
Output: USB 5V/3A 9V/2A 12V/1.67A 10V/2.25A 12V/1.5A(22.5W Max.)
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)
Output: Built-in-Lightning 5V,2A(10W)

Specifications

22.5W

Material: ABS
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A(22.5W Max.)
Output: USB 5V/3A 9V/2A 12V/1.67A 10V/2.25A 12V/1.5A(22.5W Max.)
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)
Output: Built-in-Lightning 5V,2A(10W)

POWER BANK WITH BUILT-IN CABLE



ITC-T2527
20000mAh(114373*4)
Specs: 22.5W
Size: 126.3*52*49.5mm



ITC-T2532
10000mAh(21700*2)
Specs: 22.5W
Size: 82*50.1*38.5mm



Solar Power Bank
10000mAh Power Bank
PD 20W Fast Charging
Multiple battery life
ITC-PB10SL
10000mAh(1260110*1)
Specs: 2A/PD20W/22.5W
Size: 148.8*68.5*18mm



ITC-SL10
10000mAh(9065113*1)
Specs: 2A/PD20W/22.5W
Size: 152*73.3*14.5mm

Specifications
22.5W
Material: ABS
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A(22.5W Max.)
Output: USB 5V/3A 9V/2A 12V/1.67A 10V/2.25A 12V/1.5A(22.5W Max.)
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)
Output: Built-in-Lightning 5V/2A(10W)

Specifications
22.5W
Material: ABS
Input: Type-C 5V/3A 9V/2A 12V/1.5A(18W Max.)
Output: Type-C 5V/3A 9V/2.22A 12V/1.67A
Output: Built-in Type-C 5V/3A 9V/2.22A 12V/1.67A 10V/2.25A(22.5W Max.)
Output: Built-in-Lightning 5V/2A(10W)

Specifications
2A
Material: ABS
Input: Type-C 5V/2A
Output: Type-C 5V/2A
Output: USB 5V/2A
Solar Panel Monocrystalline Silicon, 130mA

Specifications
22.5W/PD20W
Material: ABS
Input: Type-C 5V/2.4A 9V/2A 12V/1.5A
Output: Type-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB 5V/3A 9V/2A 10V/2.25A 12V/1.5A 22.5W Max
Solar Panel Monocrystalline Silicon, 130mA

Specifications
2A
Material: ABS
Input: Type-C 5V/2A
Output: Type-C 5V/2A
Output: USB 1/2 5V/2A
Solar Panel Monocrystalline Silicon, 130mA

Specifications
22.5W/PD20W
Material: ABS
Input: Type-C 5V/2.4A 9V/2A 12V/1.5A
Output: Type-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB 1/2 5V/3A 9V/2A 10V/2.25A 12V/1.5A 22.5W Max
Solar Panel Monocrystalline Silicon, 130mA

15W Magnetic Wireless Power Bank

5000mAh-10000mAh Capacity



Stronger Magnetic
Connection



Smart Display On Demand

MAGNETIC WIRELESS POWER BANK WITH TFT SCREEN



MAC05T/MAC05TB
5000mAh

MAC10T/MAC10TB
10000mAh



MACC05TK/MACC05T
5000mAh

MACC10TK/MACC10T
10000mAh

Specifications

22.5W+15W

Material: ABS
Capacity: 5000mAh (955465*1)
Input: Type-C port 5V/3A 9V/2A (if any)
Output: Type-C port 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Input: Built-in TYPE C cable 5V/3A 9V/2A (if any)
Output: Built-in TYPE C cable 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic wireless 15W Max
Size: 94.6*63.5*14mm

Specifications

22.5W+15W

Material: ABS
Capacity: 10000mAh (145675*1)
Input: Type-C port 5V/3A 9V/2A (if any)
Output: Type-C port 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Input: Built-in TYPE C cable 5V/3A 9V/2A (if any)
Output: Built-in TYPE C cable 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic wireless 15W Max
Size: 104.5*64.5*18.5mm

MAGNETIC WIRELESS POWER BANK



MAC05D/MAC05L
5000mAh



MAC10D/MAC10L
10000mAh



MAC05DB/MAC05LB
5000mAh

MAC10DB/MAC10LB
10000mAh



MAC05DK/MAC05LK
5000mAh

MAC10DK/MAC10LK
10000mAh



MCC05D/MCC05L
5000mAh

MCC10D/MCC10L
10000mAh



MACC10DH/MACC10LH
10000mAh

Specifications

22.5W+15W

Material: ABS
Capacity: 5000mAh (955465*1)
Input: Type-C port 5V/3A 9V/2A
Output: Type-C port 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A
Input: Built-in TYPE C cable 5V/3A 9V/2A (if any)
Output: Built-in TYPE C cable 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic wireless 15W Max
Size: 94*63.5*14mm

Specifications

22.5W+15W

Material: ABS
Capacity: 10000mAh (145675*1)
Input: Type-C port 5V/3A 9V/2A
Output: Type-C port 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A
Input: Built-in TYPE C cable 5V/3A 9V/2A (if any)
Output: Built-in TYPE C cable 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic wireless 15W Max
Size: 104.5*64.5*18.5mm

Specifications

22.5W+15W

Material: ABS
Capacity: 5000mAh (955465*1)
Input: Type-C port 5V/3A 9V/2A (if any)
Output: Type-C port 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Input: Built-in TYPE C cable 5V/3A 9V/2A (if any)
Output: Built-in TYPE C cable 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic wireless 15W Max
Size: 96*63.5*14mm

Specifications

22.5W+15W

Material: ABS
Capacity: 10000mAh (145675*1)
Input: Type-C port 5V/3A 9V/2A (if any)
Output: Type-C port 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A (if any)
Input: Built-in TYPE C cable 5V/3A 9V/2A
Output: Built-in TYPE C cable 5V/3A 9V/2.22A 10V/2.25A 12V/1.67A
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A (if any)
Output: Magnetic wireless 15W Max
Size: 104.5*64.5*21.35mm (for ITC-MACC10DH&ITC-MACC10LH)
Size: 105*64.5*18.5mm

POWER BANK WITH BUILT-IN CABLE

POWER BANK WITH BUILT-IN CABLE



ITC-PB10L
10000mAh(1260110*1)

Specs: 2A/22.5W
Size: 148.8*68.5*18mm



ITC-PB10LC2
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*18mm



ITC-PB10LC4
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*18mm



ITC-PB10S
10000mAh(1260110*1)

Specs: 2A/22.5W
Size: 148.8*68.5*18mm



ITC-PB10SC2
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*18mm



ITC-PB10SC4
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*18mm



ITC-PB10T
10000mAh(1260110*1)

Specs: 2A/22.5W
Size: 148.8*68.5*19.1mm



ITC-PB10TC2
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*19.1mm



ITC-PB10TC4
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*19.1mm



ITC-PB10D
10000mAh(1260110*1)

Specs: 2A/22.5W
Size: 148.8*68.5*19.1mm



ITC-PB10DC2
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*19.1mm



ITC-PB10DC4
10000mAh(1260110*1)

Specs: 22.5W
Size: 148.8*68.5*19.1mm



ITC-PB20L
20000mAh(1260110*2)

Specs: 2A/22.5W
Size: 148.8*68.5*30mm



ITC-PB20LC2
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*30mm



ITC-PB20LC4
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*30mm



ITC-PB20S
20000mAh(1260110*2)

Specs: 2A/22.5W
Size: 148.8*68.5*30mm



ITC-PB20SC2
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*30mm



ITC-PB20SC4
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*30mm



ITC-PB20T
20000mAh(1260110*2)

Specs: 2A/22.5W
Size: 148.8*68.5*31.1mm



ITC-PB20TC2
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*31.1mm



ITC-PB20TC4
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*31.1mm



ITC-PB20D
20000mAh(1260110*2)

Specs: 2A/22.5W
Size: 148.8*68.5*31.1mm



ITC-PB20DC2
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*31.1mm



ITC-PB20DC4
20000mAh(1260110*2)

Specs: 22.5W
Size: 148.8*68.5*31.1mm

Specifications

2A

Material: ABS
Input: Type-C port 5V/2A
Output: Type-C port 5V/2A (Optional)
Output: USB-A port 5V/2A

Specifications

22.5W

Material: ABS
Input: Type-C port 5V/3A 9V/2A 12V/1.5A
Output: Type-C port 5V/3A 9V/2.22A 12V/1.67A (20W Max.)
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A(22.5W Max.)
Input: Built-in USB-A cable 5V/2A
Output: Built-in Micro cable 5V/2A (10W Max.)
Input: Built-in Type-C cable 5V/3A 9V/2A 12V/1.5A
Output: Built-in Type-C cable 5V/3A 9V/2.22A 12V/1.67A(20W Max.)
Output: Built-in Lightning cable 5V/3A 9V/2A 12V/1.67A(20W Max.)

Specifications

2A

Material: ABS
Input: Type-C port 5V/2A
Output: Type-C port 5V/2A (Optional)
Output: USB-A port 5V/2A

Specifications

22.5W

Material: ABS
Input: Type-C port 5V/3A 9V/2A 12V/1.5A
Output: Type-C port 5V/3A 9V/2.22A 12V/1.67A (20W Max.)
Output: USB-A port 5V/3A 9V/2A 10V/2.25A 12V/1.5A(22.5W Max.)
Input: Built-in USB-A cable 5V/2A
Output: Built-in Micro cable 5V/2A (10W Max.)
Input: Built-in Type-C cable 5V/3A 9V/2A 12V/1.5A
Output: Built-in Type-C cable 5V/3A 9V/2.22A 12V/1.67A(20W Max.)
Output: Built-in Lightning cable 5V/3A 9V/2A 12V/1.67A(20W Max.)

New design power bank

Easy charge cables



2 cables



4 cables



Digital display



TFT display



10000mAh



20000mAh

POWER BANK WITH LiFePO₄ BATTERY



ITC-A03-1

10000mAh(1260105*1)

Specs: 2A/22.5W
Size: 148.6*69*16.2mm



ITC-A03-2

10000mAh(1260105*1)

Specs: 2A/22.5W
Size: 148.6*69*16.2mm



ITC-A03-3

10000mAh(1260105*1)

Specs: 2A/22.5W
Size: 148.6*69*16.2mm



ITC-A03-4

10000mAh(1260105*1)

Specs: 2A/22.5W
Size: 148.6*69*16.2mm



ITC-B03-1

10000mAh(1260105*1)

Specs: 2A/22.5W
Size: 148.6*69*16.2mm



ITC-B03-2

10000mAh(1260105*1)

Specs: 2A/22.5W
Size: 148.6*69*16.2mm



ITC-A04-1

20000mAh(1260105*2)

Specs: 2A/22.5W
Size: 148.6*69*28.2mm



ITC-A04-2

20000mAh(1260105*2)

Specs: 2A/22.5W
Size: 148.6*69*28.2mm



ITC-A04-3

20000mAh(1260105*2)

Specs: 2A/22.5W
Size: 148.6*69*28.2mm



ITC-A04-4

20000mAh(1260105*2)

Specs: 2A/22.5W
Size: 148.6*69*28.2mm



ITC-B04-1

20000mAh(1260105*2)

Specs: 2A/22.5W
Size: 148.6*69*28.2mm



ITC-B04-2

20000mAh(1260105*2)

Specs: 2A/22.5W
Size: 148.6*69*28.2mm

Specifications

2A(ACC port)

Material: ABS

Input: TYPE-C 5V/2A 12V/1.5A

Output: TYPE-C 5V/3A 9V/2.22A 12V/1.67A

Output: USB 5V/2A

Specifications

22.5W(ACC or ACA port)

Material: ABS

Input: TYPE-C 5V/2.4A 9V/2A 12V/1.5A

Output: TYPE-C 5V/3A 9V/2.22A 12V/1.67A

Output: USB 5V/3A 9V/2.22A 12V/1.67A SCOP10V/2.25A

SUPER SLIM POWER BANK
SOLID-STATE BATTERIES ARE AVAILABLE



ITC-M01S



ITC-M02



ITC-M01



ITC-M03



ITC-M04



ITC-N01S



ITC-N02



ITC-N01



ITC-N03



ITC-N04



ITC-N01SM
5000mAh(706074)

Specs: 2A/PD20W/22.5W
Size: 103.8*68*10mm



ITC-N02M
10000mAh(146074)

Specs: 2A/PD20W/22.5W
Size: 103.8*68*17mm



ITC-N01M
5000mAh(5758102)

Specs: 2A/PD20W/22.5W
Size: 131.8*66.2*10.5mm



ITC-N03M
10000mAh(9858102)

Specs: 2A/PD20W/22.5W
Size: 131.8*66.2*13.2mm



ITC-N04M
20000mAh(9858102*2)

Specs: 2A/PD20W/22.5W
Size: 131.8*66.2*23mm

SUPER SLIM ALUMINUM ALLOY POWER BANK
SOLID-STATE BATTERIES ARE AVAILABLE



ITC-ML01



ITC-ML03



ITC-ML04



ITC-NL01



ITC-NL03



ITC-NL04



ITC-NL01M
5000mAh(5758102)

Specs: 2A/PD20W/22.5W
Size: 130.5*62.5*8.8mm



ITC-NL03M
10000mAh(9858102)

Specs: 2A/PD20W/22.5W
Size: 130.5*62.5*12.2mm



ITC-NL04M
20000mAh(9858102*2)

Specs: 2A/PD20W/22.5W
Size: 130.5*62.5*22mm

SUPER SLIM ALUMINUM ALLOY POWER BANK
SOLID-STATE BATTERIES ARE AVAILABLE



ITC-MS01
5000mAh(606280)

Specs: 2A/PD20W/22.5W
Size: 108.5*66.5*8.8mm



ITC-MS01-M
5000mAh(536280/546280)

Specs: 2A+5W/22.5W+15W
Size: 108.5*66.5*8.8mm



ITC-MS03
10000mAh(126280)

Specs: 2A/PD20W/22.5W
Size: 108.5*66.5*14.8mm



ITC-MS04
20000mAh(126280*2)

Specs: 2A/PD20W/22.5W
Size: 108.5*66.5*26.8mm



ITC-MX01
5000mAh(706074)

Specs: 2A/PD20W/22.5W
Size: 102.5*64.5*9.8mm



ITC-MX01-M
5000mAh(606074/706074)

Specs: 2A+5W/22.5W+15W
Size: 102.5*64.5*9.8mm



ITC-MX03
10000mAh(1376074)

Specs: 2A/PD20W/22.5W
Size: 102.5*64.5*16.5mm



ITC-MX04
20000mAh(1376074*2)

Specs: 2A/PD20W/22.5W
Size: 102.5*64.5*30.2mm



ITC-NS01
5000mAh(606280)

Specs: 2A/PD20W/22.5W
Size: 108.5*66.5*8.8mm



ITC-NS03-M
10000mAh(126280)

Specs: 2A+5W/22.5W+15W
Size: 108.5*66.5*15.8mm



ITC-NS03
10000mAh(126280)

Specs: 2A/PD20W/22.5W
Size: 108.5*66.5*14.8mm



ITC-NS04
20000mAh(126280*2)

Specs: 2A/PD20W/22.5W
Size: 108.5*66.5*26.8mm



ITC-NX01
5000mAh(706074)

Specs: 2A/PD20W/22.5W
Size: 102.5*64.5*9.8mm



ITC-MX03-M
10000mAh(1376074)

Specs: 2A+5W/22.5W+15W
Size: 102.5*64.5*17.5mm



ITC-NX03
10000mAh(1376074)

Specs: 2A/PD20W/22.5W
Size: 102.5*64.5*16.5mm



ITC-NX04
20000mAh(1376074*2)

Specs: 2A/PD20W/22.5W
Size: 102.5*64.5*30.2mm

Specifications

2A

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

2A

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/2A
Output: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

PD20W

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/3A 9V/2A 12V/1.5A
Output: USB2 5V/3A 9V/2A 12V/1.5A

Specifications

22.5W

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/2.4A 9V/2A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.67A
Output: USB1 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: USB2 5V/3A 9V/2A 10V/2.25A 12V/1.5A

Specifications

22.5W+15W

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/3A 9V/2A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 10V/2.25A 12V/1.67A
Output: USB 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic Wireless 15W/10W/7.5W/5W

Specifications

2A

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

2A

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/2A
Output: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

PD20W

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/3A 9V/2A 12V/1.5A
Output: USB2 5V/3A 9V/2A 12V/1.5A

Specifications

22.5W

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/2.4A 9V/2A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: USB2 5V/3A 9V/2A 10V/2.25A 12V/1.5A

Specifications

22.5W+15W

Material: ABS(front)+Aluminum alloy(Back)
Input: TYPE-C 5V/3A 9V/2A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 10V/2.25A 12V/1.67A
Output: USB 5V/3A 9V/2A 10V/2.25A 12V/1.5A
Output: Magnetic Wireless 15W/10W/7.5W/5W



ITC-D01
5000mAh

Specs: 2A
Size: 100*63.8*15.8mm



ITC-D02
10000mAh

Specs: 2A/PD20W/22.5W
Size: 100*63.8*26.8mm



ITC-D03
10000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.8*17.5mm



ITC-D04
20000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.8*28mm



ITC-D05
30000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.8*40mm



ITC-S1
5000mAh

Specs: 2A
Size: 100*63.3*13.5mm



ITC-S2
10000mAh

Specs: 2A/PD20W/22.5W
Size: 100*63.3*23mm



ITC-S3
10000mAh

Specs: 2A/PD20W/22.5W
Size: 152*73.3*14.5mm



ITC-S4
20000mAh

Specs: 2A/PD20W/22.5W
Size: 152*73.3*23.8mm



ITC-S5
10000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.44*15.7mm



ITC-S6
20000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.44*27.7mm



ITC-P01
5000mAh

Specs: 2A
Size: 100*63.8*15.8mm



ITC-P02
10000mAh

Specs: 2A/PD20W/22.5W
Size: 100*63.8*26.8mm



ITC-P03
10000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.8*17.5mm



ITC-P04
20000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.8*28mm



ITC-P05
30000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.8*40mm



ITC-T1
5000mAh

Specs: 2A
Size: 100*63.3*13.5mm



ITC-T2
10000mAh

Specs: 2A/PD20W/22.5W
Size: 100*63.3*23mm



ITC-T3
10000mAh

Specs: 2A/PD20W/22.5W
Size: 152*73.3*14.5mm



ITC-T4
20000mAh

Specs: 2A/PD20W/22.5W
Size: 152*73.3*23.8mm



ITC-T5
10000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.44*15.7mm



ITC-T6
20000mAh

Specs: 2A/PD20W/22.5W
Size: 140*68.44*27.7mm

Specifications

2A

Material: ABS
Input: MICRO 5V/2A
Input: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

2A

Material: ABS
Input: MICRO 5V/2A
Input: TYPE-C 5V/2A
Output: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

PD20W

Material: ABS
Input: MICRO 5V/2A 9V/2A
Input: TYPE-C 5V/2A 9V/2A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/3A 9V/2A 12V/1.5A
Output: USB2 5V/3A 9V/2A 12V/1.5A

Specifications

22.5W

Material: ABS
Input: MICRO 5V/2A 9V/2A
Input: TYPE-C 5V/2A 9V/2A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/4.5A 4.5V/5A 5V/3A 9V/2A 12V/1.5A
Output: USB2 5V/4.5A 4.5V/5A 5V/3A 9V/2A 12V/1.5A

Specifications

2A

Material: ABS
Input: MICRO 5V/2A
Input: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

2A

Material: ABS
Input: MICRO 5V/2A
Input: TYPE-C 5V/2A
Output: TYPE-C 5V/2A
Output: USB1 5V/2A
Output: USB2 5V/2A

Specifications

PD20W

Material: ABS
Input: MICRO 5V/2A 9V/2A
Input: TYPE-C 5V/2A 9V/2A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/3A 9V/2A 12V/1.5A
Output: USB2 5V/3A 9V/2A 12V/1.5A

Specifications

22.5W

Material: ABS
Input: MICRO 5V/2A 9V/2A
Input: TYPE-C 5V/2A 9V/2A 12V/1.5A
Output: TYPE-C 5V/3A 9V/2A 9V/2.22A 12V/1.5A
Output: USB1 5V/4.5A 4.5V/5A 5V/3A 9V/2A 12V/1.5A
Output: USB2 5V/4.5A 4.5V/5A 5V/3A 9V/2A 12V/1.5A



ITC-MP01

5000mAh*4PCS(21700*1)

Specs: PD20W
Size: 79.2*38.2*25.5mm



ITC-MP02

5000mAh*4PCS(21700*1)

Specs: PD20W
Size: 88*39.2*30.7mm



ITC-PZ01

5000mAh(21700*1)

Specs: PD20W
Size: 79.2*38.2*25.5mm



ITC-PW01

5000mAh(21700*1)

Specs: PD20W
Size: 88*39.2*30.7mm



ITC-PZ02

5000mAh(21700*1)

Specs: PD20W
Size: 79.14*46.15*27mm



ITC-PZ03TWS

5000mAh(21700*1)

Specs: 22.5W
Size: 82.6*42.5*28.6mm

Specifications

PD20W

Material: ABS
Input: (Power Bank)Pogo Pin 9V/2A
USB-C1 5V/2A 9W/2A
USB-C2 5V/3A 9W/2A
Output : (Power Bank)USB-C2 or LT 5V/3A 9W/2.22A 12V/1.67A
Input: (Dock)USB-C 5V/2.5A
Output: (Dock)Pogo Pin1/2/3/4 9V/2A

Specifications

PD20W

Material: ABS
Input: (Power Bank)Pogo Pin 9V/2A
USB-C1 5V/2A 9W/2A
USB-C2 5V/3A 9W/2A
Output : (Power Bank)USB-C2 or LT 5V/3A 9W/2.22A 12V/1.67A
Input: (Dock)USB-C 5V/2.5A
Output: (Dock)Pogo Pin1/2/3/4 9V/2A

Specifications

PD20W

Material: ABS
Input: Type-C1 5V/2A 9W/2A 18W
Input: Type-C2 5V/3A 9W/2A 18W
Output: Type-C USB-C2 or LT 5V/3A 9W/2.22A 12V/1.67A 20W

Specifications

PD20W

Material: ABS
Input: Type-C Type-C & LT 2in1 connector: 5V/2A 9W/2A 18W
Output: Type-C Type-C & LT 2in1 connector: 5V/3A 9W/2.22A 12V/1.67A 20W
Output: Built-in Type-C or Lightning Cable: 5V/3A 9W/2.22A 12V/1.67A 20W

Specifications

22.5W

Material: fire-resistant ABS
Input: Type-C 5V/3A 9W/2A 12V/1.5A(Max18W)
Output: Type-C 5V/3A 9W/2.22A 10V/2.25A 12V/1.67A(Max 22.5W)
Output Built-in Type-C 5V/3A 9W/2.22A 12V/1.67A 10V/2.25A(Max22.5W)

LAPTOP POWER BANK

Solid-State batteries, 1000+ cycle life
20000-30000mAh, PD30W 45W 65W 100W & 140W



ITC-HP01/ITC-HP02

20000mAh/30000mAh(6060100*4/6060100*5)

Size: 146*132*17.8mm/146*132*23.8mm
Specs: PD65W/PD100W
Material: ABS
Input: Type-C1 5V=3A
Input: Type-C2 5V=3A 9V=3A 12V=3A 15V=3A 20V=3A(60W Max.)
Output: Type-C2 5V=3A 9V=3A 12V=3A 15V=3A 20V=3.25A(65W Max)/30V=3.25A(100W)
Input: Type-C3 Built in Cable 5V=3A 9V=3A 12V=3A 15V=3A 20V=3A(60W Max.)
Output: Type-C3 Built in Cable 5V=3A 9V=3A 12V=3A 15V=3A 20V=3.25A(65W Max)/30V=3.25A(100W)
Output: USB 5V=3A 9V=2A 10V=2.25A 12V=1.5A(22.5W Max.)



60W IN

100W OUT

22.5W OUT



ITC-T2426

20000mAh(126280*2)

Specs: PD35W
Size: 116.7*70.5*27.7mm



ITC-C01

9600mAh/10000mAh(18650*3)

Specs: PD45W
Size: 100*62.5*22.5mm



ITC-T6&ITC-P4

20000mAh(6060100*4)

Specs: PD65W
Size: 140*68*27.7mm

Specifications

PD35W

Material: ABS
Input: Type-C 5V/3A 9V/3A 12V/2.9A 15V/2.3A 20V/1.75A
Output: Type-C 5V/3A 9V/3A 12V/2.9A 15V/2.3A 20V/1.75A
Output: USB 5V/3A 9V/2A 12V/1.5A 10V/2.25A
Input: Built-in Type-C cable 5V/3A 9V/3A 12V/2.9A 15V/2.3A 20V/1.75A
Output: Built-in Type-C cable 5V/3A 9V/3A 12V/2.9A 15V/2.3A 20V/1.75A

Specifications

PD45W

Material: ABS
Input: TYPE-C 5V/3.0A 9V/2.0A 12V/1.67A 15V/2A 20V/1.5A(30W max)
Output: TYPE-C 5V/3.0A 9V/3A 12V/3A 15V/3A 20V/2.25A(45W max)
PPS: 3.3V-11V/3A, 3.3V-16V/3A
Output: USB 5V/3A 9V/2A 12V/1.67A(20W max)
IC solution: with OCP,OVP,ODP,SCP,OTP

Specifications

PD65W

Material: ABS
Input: Micro 5V/2A 9V/2A 12V/1.5A(18W)
Input: Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W)
Output: Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3.25A(65W max)
Output: USB 1/2 4.5V/5A 5V/5A 5V/2.4A 12V/1.5A(25W)
IC solution: with OCP,OVP,ODP,SCP,OTP



ITC-P5

25000mAh(6060100*5)

Specs: PD100W
Size: 140*68*39.7mm



ITC-P5

30000mAh(6060100*6)

Specs: PD140W
Size: 140*68*39.7mm



ITC-S6&ITC-D4

20000mAh(6060100*4)

Specs: PD45W
Size: 140*68*27.7mm



ITC-S6&ITC-D4

20000mAh(6060100*4)

Specs: PD65W
Size: 140*68*27.7mm



ITC-D5

25000mAh(6060100*5)

Specs: PD100W
Size: 140*68*39.7mm



ITC-D5

30000mAh(6060100*6)

Specs: PD140W
Size: 140*68*39.7mm

Specifications

PD100W

Material: ABS

USB-C1 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 100W Max

USB-C2 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 100W Max

USB-A1 Output: 5V/3A 9V/2A 10V/2.25A 12V/1.5A 22.5W Max

IC solution: with OCP,OVP,ODP,SCP,OTP

Specifications

PD140W

Material: ABS

USB-C1 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 140W Max

USB-C2 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 140W Max

USB-A1 Output: 5V/3A 9V/2A 10V/2.25A 12V/1.5A 22.5W Max

IC solution: with OCP,OVP,ODP,SCP,OTP

Specifications

PD45W

Material: ABS+rubber oil

Input: Micro 5V/2A 9V/2A (18W max)

Input: Type-C 5V/3.0A 9V/2.0A 12V/1.5 15V/2.66A 20V/2A(40W max)

Output: Type-C 5V/3.0A 9V/3A 12V/3A 15V/3A 20V/2.25A(45W max)

Output: USB 1/2 4.5V/5A 5V/5A 5V/2.4A 9V/2A 12V/1.5A(25W max)

IC solution: with OCP,OVP,ODP,SCP,OTP

Specifications

PD65W

Material: ABS+rubber oil

Input: Micro 5V/2A 9V/2A 12V/1.5A(18W)

Input: Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W)

Output: Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3.25A(65W max)

Output: USB 1/2 4.5V/5A 5V/5A 5V/2.4A 9V/2A 12V/1.5A(25W)

IC solution: with OCP,OVP,ODP,SCP,OTP

Specifications

PD100W

Material: ABS

USB-C1 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 100W Max

USB-C2 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 100W Max

USB-A1 Output: 5V/3A 9V/2A 10V/2.25A 12V/1.5A 22.5W Max

IC solution: with OCP,OVP,ODP,SCP,OTP

Specifications

PD140W

Material: ABS

USB-C1 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 140W Max

USB-C2 Input/Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 140W Max

USB-A1 Output: 5V/3A 9V/2A 10V/2.25A 12V/1.5A 22.5W Max

IC solution: with OCP,OVP,ODP,SCP,OTP



ITC-PD02

10000mAh(18650*4)

Specs: PD100W
Size: 147*45*34mm



ITC-PD01

10000mAh(18650*4)

Specs: PD100W
Size: 147*45*34mm



ITC-PD03

20000mAh(21700*4)

Specs: PD100W
Size: 147*52*48mm



ITC-PD04

20000mAh(21700*4)

Specs: PD100W
Size: 147*52*48mm

Specifications

PD100W

Material: ABS+PC
Input: TYPE-C port 5V/3A 9V/3A 12V/3A 15V/3A 20V/5.0A (100W Max)
Output: TYPE-C port 5V/3A 9V/3A 12V/3A 15V/3A 20V/5.0A 3.3~21V/5A PPS (100W Max)
Input: Built-in TYPE-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/5.0A (100W Max)
Output: Built-in TYPE-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/5.0A 3.3~21V/5A PPS (100W Max)
Output: USB 5.0V/3.0A 9V/2.22A 10V/2.25A 12V/1.67A (22.5W Max)

Specifications

PD100W

Material: ABS+PC
Input: TYPE-C port 5V/3A 9V/3A 12V/3A 15V/3A 20V/5.0A (100W Max)
Output: TYPE-C port 5V/3A 9V/3A 12V/3A 15V/3A 20V/5.0A 3.3~21V/5A PPS (100W Max)
Output: USB 5.0V/3.0A 9V/2.22A 10V/2.25A 12V/1.67A (22.5W Max)

Specifications

PD100W

Material: ABS+PC
Input: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W Max)
Input: Type-C 2 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W Max)
Output: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)
Output: Type-C 2 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)
Output: USB 5.0V/2.1A 9V/2.0A 10V/2.25A 12V/1.5A(22.5W Max)

Specifications

PD100W

Material: ABS+PC
Input: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W Max)
Output: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)
Output: USB 5.0V/2.1A 9V/2.0A 10V/2.25A 12V/1.5A(22.5W Max)
Input: Built-in Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)
Output: Built-in Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)



ITC-PD03L

20000mAh(21700*4)

Specs: PD100W
Size: 147*52*48mm



ITC-PD04L

20000mAh(21700*4)

Specs: PD100W
Size: 147*52*48mm

Specifications

PD100W

Material: ABS+PC

Input: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W Max)

Input: Type-C 2 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W Max)

Output: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)

Output: Type-C 2 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)

Output: USB 5.0V/2.1A 9V/2.0A 10V/2.25A 12V/1.5A(22.5W Max)

Specifications

PD100W

Material: ABS+PC

Input: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A(60W Max)

Output: Type-C 1 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)

Output: USB 5.0V/2.1A 9V/2.0A 10V/2.25A 12V/1.5A(22.5W Max)

Input: Built-in Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)

Output: Built-in Type-C 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A 20V/5.0A(100W Max)



ITC-G05



ITC-G03



ITC-U01



ITC-U02



ITC-T2410



ITC-T2411



ITC-G02



ITC-Q01



ITC-Q02



ITC-Q03



ITC-U03



ITC-U04



ITC-LM05



ITC-LM06



ITC-C48



ITC-LM01



ITC-T2413-1



ITC-T2413-2



ITC-T2419



ITC-T2420



ITC-T2421



ITC-S8-M



ITC-S9-M



ITC-S1-M



ITC-S2-M



ITC-LM02



ITC-LM03



ITC-AP01



ITC-AP02



ITC-T2427-2



ITC-T2431-2



ITC-T2435



ITC-T2502-1



ITC-LM02C



ITC-LM03C



ITC-LM02H



ITC-LM02CH



ITC-LM03H



ITC-LM03CH



ITC-T2300P



ITC-T2310P



ITC-T2311P



ITC-T2401



ITC-T2340



ITC-T2347



ITC-T2348



ITC-T2349



ITC-T2423-3



ITC-T2424-3



ITC-T2430-3



ITC-T2432-3



ITC-T2438-3



ITC-T2434-3



ITC-T2504-3



ITC-P03S



ITC-P04S



ITC-P05S



ITC-P03SC



ITC-P04SC



ITC-P05SC



ITC-Q14



ITC-A03-1S ITC-A04-1S ITC-B03-2 ITC-B04-2 ITC-J02 ITC-J04 ITC-G01 ITC-AC01



ITC-K01 ITC-K02 ITC-K03 ITC-K01C2/K02C2



ITC-H01C2 ITC-H02C2 ITC-H03C2



ITC-Q15 ITC-LM18 ITC-LM19 ITC-Q05 ITC-Q10 ITC-Q12

